

## **ALPHA 25W**

# Adjustable Tracklight

Track lighting is used because of its flexibility in positioning fittings, and removing or adding fittings to achieve the correct luminance levels. It can focus the viewer's attention onto a piece of art work or display.

Alpha S perfectly combines design and function. Optimized passive cooling system ensures low temperature and long lifetime of LED.

The Alpha Track Light is an architectural design, a high lighting quality, with optimised efficiency. Ideal for museums, art galleries, restaurants and reception areas.







#### **SPECIFICATIONS**

#### **Material Specifications**

MaterialAluminiumFinishPowder Coat

DimensionsHead 72mm Dia x 137mm(L)Adjustment90° tilt, 359° rotation

Application 3-Wire Track

OptionsBlack Ring, Oblique RingWarranty5 Year Replacement

## **Electrical Specifications**

**Power Supply** Integrated Tridonic Driver 700mA, Non-

Dimmable

Input Voltage 240°

**Connection Method** 3 Circuit Track. Sold Separately

## **Optic Specifications**

**Light Source** 28W Citizen LED

**Beam Angle** 40° (12°/18°/ 25° options)

 CRI
 90Ra

 Colour Deviation
 SDCM ≤ 3

 Reported L70 (Hours)
 > 54,000 Hrs

## VARIATIONS

LC5100-40	ALPHA 25W Tracklight, White, 40°, Non-Dim, 3000K, 1900lm
LC5101-40	ALPHA 25W Tracklight, White, 40°, Non-Dim, 4000K, 2000lm
LC5106-40	ALPHA 25W Tracklight, Black, 40°, Non-Dim, 3000K, 1900lm
LC5106-18	ALPHA 25W Tracklight, Black, 18°, Non-Dim, 3000K, 1900lm
LC5186-40	ALPHA 25W Tracklight, Black, 40°, Non-Dim, 4000K, 2000lm







