

ALPHA-M38W

Adjustable Tracklight

Track lighting is used because of its flexibility in positioning fittings, and removing or adding fittings to achieve the correct luminance levels. It can focus the viewer's attention onto a piece of art work or display.

Alpha S perfectly combines design and function. Optimized passive cooling system ensures low temperature and long lifetime of LED.

The Alpha Track Light is an architectural design, a high lighting quality, with optimised efficiency. Ideal for museums, art galleries, restaurants and reception areas.



IP20



SPECIFICATIONS

Material Specifications

MaterialAluminiumFinishPowder Coat

DimensionsHead 90mm Dia x 220mm(L)Adjustment90° tilt, 359° rotationApplication3-Wire Track

OptionsBlack Ring, Oblique RingWarranty5 Year Replacement

Electrical Specifications

Power Supply Integrated Tridonic Driver 700mA, Non-Dim

Input Voltage 240V

Connection Method 3 Circuit Track. Sold Separately

Optic Specifications

Light Source 38W Citizen LED

Beam Angle 35° (18°/25°/50° options)

 CRI
 90Ra

 Colour Deviation
 SDCM ≤ 3

 Reported L70 (Hours)
 > 54,000 Hrs

VARIATIONS

 LC5102
 ALPHA-M 38W Tracklight, White, 35°, Non-Dim, 3000K, 2890Im

 LC5103
 ALPHA-M 38W Tracklight, White, 35°, Non-Dim, 4000K, 3040Im

 LC5102B
 ALPHA-M 38W Tracklight, Black, 35°, Non-Dim, 3000K, 2890Im

 LC5103B
 ALPHA-M 38W Tracklight, Black, 35°, Non-Dim, 4000K, 3040Im

 LC5102D
 ALPHA-M 38W Tracklight, White, 35°, DALI, 3000K, 2890Im







