

# 1300 827 284

www.decrolux.com.au

**Classic Series** 

Proven. Quality. Customisable

# **ALPHA-M38W** Adjustable Tracklight

Track lighting is used because of its flexibility in positioning fittings, and removing or adding fittings to achieve the correct luminance levels. It can focus the viewer's attention onto a piece of art work or display.

Alpha S perfectly combines design and function. Optimized passive cooling system ensures low temperature and long lifetime of LED.

The Alpha Track Light is an architectural design, a high lighting quality, with optimised efficiency. Ideal for museums, art galleries, restaurants and reception areas.

> Aluminium Powder Coat

240V

90Ra SDCM ≤ 3

38W Citizen LED

> 54,000 Hrs

35° (18°/25°/50° options)

Head 90mm Dia x 220mm(L) 90° tilt, 359° rotation 3-Wire Track

Integrated Tridonic Driver 700mA, Non-Dim

3 Circuit Track. Sold Separately

Black Ring, Oblique Ring 5 Year Replacement



## SPECIFICATIONS

## **Material Specifications**

Material
Finish
Dimensions
Adjustment
Application
Options
Warranty

### **Electrical Specifications**

**Power Supply** Input Voltage **Connection Method** 

### **Optic Specifications**

Light Source **Beam Angle** CRI **Colour Deviation Reported L70 (Hours)** 

## VARIATIONS

LC5102	ALPHA-M 38W Tracklight, White, 35°, Non-Dim, 3000K, 2890Im
LC5103	ALPHA-M 38W Tracklight, White, 35°, Non-Dim, 4000K, 3040Im
LC5102B	ALPHA-M 38W Tracklight, Black, 35°, Non-Dim, 3000K, 2890lm
LC5103B	ALPHA-M 38W Tracklight, Black, 35°, Non-Dim, 4000K, 3040Im
LC5102D	ALPHA-M 38W Tracklight, White, 35°, DALI, 3000K, 2890lm





1300 827 284 sales@decrolux.com.au | Latest Product Data >

