


APEX 36W

Backlit Panel Light 1200x300

dynamic series

Efficient. Cutting Edge. Reliable

The APEX 36W Backlit Panel Light features its light source positioned at the rear of the panel, ensuring even and uniform brightness. No light guide plate, no yellowing. Additionally, it operates with standard flicker-free technology, delivering a reliable and eye-friendly lighting solution.



IP40



Flicker Free




SPECIFICATIONS

Material Specifications

Material	Aluminium Frame, PS Diffuser
Finish	RAL9016 Traffic White
Dimensions	1195mm x 295mm x 30mm
Ingress Protection	IP40
Options	Suitable for T-Bar or Plaster Recess only
Weight	1.76Kg
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	MF C0650K SELV Remote Driver
Input Voltage	240V 50/60Hz
Options	DALI Available
Output Voltage	28V-40V (Driver output) Constant Current
Connection Method	Australian 2-Pin Plug & 1.2m Lead
Operating Temperature (Ta)	-25°C to +40°C



Optic Specifications

Light Source	2835 SMD
Nominal Lumens	3600lm (4000K)
CRI	80Ra
Beam Angle	120°
Colour Deviation	SDCM ≤ 5
UGR	<22
Reported L70 (Hours)	>54,000 Hrs

VARIATIONS

LC7715	Apex 36W 1200x300 Panel Light, White, Non-Dim, 4000K
---------------	------------------------------------------------------