

APEX 36W

Backlit Panel Light 600x600

dynamic series

Efficient. Cutting Edge. Reliable

APEX 36W Backlit Panel Light 600x600. These Panel lights are perfect as ceiling lights for T-BAR grid ceilings, or by using a plaster recessed frame. Ideal for commercial applications, including office spaces.

No Light Guide Plate, No Yellowing. Standard Flicker Free.



IP40



Flicker Free

SPECIFICATIONS

Material Specifications

| | |
|---------------------------|---|
| Material | Aluminium Frame, PS Diffuser |
| Finish | RAL9016 Traffic White |
| Dimensions | 595mm x 595mm x 30mm |
| Ingress Protection | IP40 |
| Options | Suitable for T-Bar or Plaster Recess only |
| Weight | 1.76Kg |
| Warranty | 5 Year Replacement |

Electrical Specifications

| | |
|-----------------------------------|--|
| Power Supply | MF C0650K SELV Remote Driver |
| Input Voltage | 240V 50/60Hz |
| Options | DALI Available |
| Output Voltage | 28V-40V (Driver output) Constant Current |
| Connection Method | Australian 2-Pin Plug & 1.2m Lead |
| Operating Temperature (Ta) | -25°C to +40°C |

Optic Specifications

| | |
|-----------------------------|-------------|
| Light Source | 2835 SMD |
| Nominal Lumens | 3773lm |
| CRI | 80Ra |
| Beam Angle | 120° |
| UGR | <22 |
| Reported L70 (Hours) | >60,000 Hrs |

VARIATIONS

| | |
|---------------|---|
| LC7705 | Apex 36W 600x600 Panel Light, White, 120°, Non-Dim, 4000K, 3773lm |
|---------------|---|

