Classic Series
Proven. Quality. Customisable

ASTON 22W
Linear Surface Mount 845mm



The ASTON 22W Surface Mount Linear Series are a sleek, modern style perfect for commercial architecture.

This sleek range is also available in suspended and recessed.

If you are building, we offer a lighting design service. Simply send us your (floor plan) and let us know your desired outcome. Our design team can make a recommendation for you.



IP44

SPECIFICATIONS

Material Specifications


Material	1.0mm Aluminium Housing, with Opal Acrylic Diffuser
Colour	Powdercoat, Black or White
Dimensions	845mm(L) x 62mm(W) x 82mm(D)
Ingress Protection	IP44
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram LED Integrated Driver, Non-Dim
Options	0-10V Dimmable
Input Voltage	240V

Optic Specifications

Light Source	Samsung 2835 SMD
LED Wattage	27W/m
Nominal Lumens	2270lm
CRI	80Ra
Beam Angle	120°
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	> 54,000 Hrs



VARIATIONS

LC8127	ASTON 22W Surface Mount Profile, 845mm, Black, Non-Dim, 3000K
LC8128	ASTON 22W Surface Mount Profile, 845mm, White, Non-Dim, 3000K
LC8129	ASTON 22W Surface Mount Profile, 845mm, Black, Non-Dim, 4000K
LC8130	ASTON 22W Surface Mount Profile, 845mm, White, Non-Dim, 4000K

Product design and technical data may be subject to change without prior notice.
Generated 29th Mar 2024 - © Decrolux
E582