

ASTON 30W

Linear Pendant 1125mm

Classic Series

Proven. Quality. Customisable

The ASTON 30W Linear Pendant 1125mm is a sleek and modern lighting solution that offers versatility and high performance. It can be suspended, surface-mounted, or recessed to fit different commercial architectural settings. With its LED technology, the pendant light provides excellent lighting quality that is energy efficient and long-lasting. The 1.0mm thick aluminum housing and opal acrylic diffuser make it both durable and stylish. Ideal for offices, retail spaces, and shopping centres, the ASTON 30W Linear Pendant 1125mm combines functionality, design, and energy efficiency to provide optimal lighting performance.



IP44



SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Opal Acrylic Diffuser
Finish	Powdercoat
Dimensions	1125mm(L) x 62mm(W) x 82mm(D)
Suspension Length	1200mm (can be customised up to 4000mm)
Ingress Protection	IP44
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram Optotronic 700mA Integrated LED Driver
Input Voltage	220V-240V, 50Hz
Operating Temperature (Ta)	-20C° to 40°C

Optic Specifications

Light Source	Samsung 2835 SMD
LED Wattage	27W/m
Delivered Lumens	2263lm (2011lm/ metre)
CRI	84Ra
R9 Value	13
Beam Angle	120°
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	>54,000 Hrs
Calculated L70 (Hours)	172,000 Hrs



VARIATIONS

LC8143	ASTON 30W Linear Pendant, 1125mm, Black, Non-Dim, 3000K
LC8144	ASTON 30W Linear Pendant, 1125mm, White, Non-Dim, 3000K
LC8145	ASTON 30W Linear Pendant, 1125mm, Black, Non-Dim, 4000K
LC8146	ASTON 30W Linear Pendant, 1125mm, White, Non-Dim, 4000K