

ASTON 45W

Direct/Indirect Pendant 1125mm

The ASTON Linear Series offers a sleek and modern style that is perfect for commercial architecture. The 45W Linear Direct/Indirect Pendant 1125mm is ideal for offices with higher ceilings, providing both ambient light and focused illumination below the fitting. Made from high-quality materials, including aluminium housing with an opal acrylic diffuser and a powder coat finish, this pendant is durable and long-lasting. With a thin profile and a range of mounting options, the ASTON Linear Series is versatile and adaptable to any commercial space.



IP44



SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Opal Acrylic Diffuser
Finish	Powdercoat
Ingress Protection	IP44
Dimensions	1125mm(L) x 62mm(W) x 82mm(D)
Suspension Length	1200mm
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram LED Driver, Non-Dim
Input Voltage	240V

Optic Specifications

Light Source	30W Direct / 15W Indirect, Samsung LB281BA+ Series 2835 SMD
Nominal Lumens	3900lm
CRI	80Ra
Beam Angle	120°
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	> 54,000 Hrs

VARIATIONS

LC8175	ASTON Linear Pendant, 30W Direct/ 15W Indirect, Black, 120°, Non-Dim, 3000K
LC8176	ASTON Linear Pendant, 30W Direct/ 15W Indirect, White, 120°, Non-Dim, 3000K
LC8177	ASTON Linear Pendant, 30W Direct/ 15W Indirect, Black, 120°, Non-Dim, 4000K
LC8178	ASTON Linear Pendant, 30W Direct/ 15W Indirect, White, 120°, Non-Dim, 4000K

Classic Series

Proven. Quality. Customisable

