

ASTON 45W

Linear Surface Mount 1685mm

The ASTON Linear Series are a sleek, modern style perfect for commercial architecture. With a thin profile, this style is available in suspended, surface mounted and recessed.

ASTON 45W Linear Surface Mount 1685mm available in Black, White, 3000K and 4000K. Modular design, for easy installation.



IP44



SPECIFICATIONS

Material Specifications

Material 1.0mm Aluminium Housing, with Opal Acrylic

Diffuser

Colour Powdercoat, Black or White

 $\textbf{Dimensions} \hspace{1cm} 1685 mm(L) \times 62 mm(W) \times 82 mm(D)$

Ingress Protection IP44

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Osram LED Integrated Driver, Non-Dim

Options 0-10V Dimmable

Input Voltage 240V

Optic Specifications

Light Source Samsung 2835 SMD

 LED Wattage
 27W/m

 Nominal Lumens
 4635lm

 CRI
 80Ra

 Beam Angle
 120°

 Colour Deviation
 SDCM ≤ 3

 Reported L70 (Hours)
 > 54,000 Hrs

VARIATIONS

LC8183	ASTON 45W Surface Mount Profile, 1685mm, Black, Non-Dim, 3000K
LC8184	ASTON45WSurfaceMountProfile, 1685mm,White,Non-Dim,3000K
LC8185	ASTON 45W Surface Mount Profile, 1685mm, Black, Non-Dim, 4000K
LC8186	ASTON 45W Surface Mount Profile, 1685mm, White, Non-Dim, 4000K
LC8184S	ASTON 45W Surface Mount Profile, 1685mm, Silver, Non-Dim, 4000K







