

# ASTON 57W

## Direct/Indirect Pendant 1405mm

**Classic Series**

Proven. Quality. Customisable

The ASTON Linear Series are a sleek, modern style perfect for commercial architecture. With a thin profile, this style is available in suspended, surface mounted and recessed.

The ASTON 57W Linear Direct/Indirect Pendant 1405mm is ideal for offices with higher ceilings. It creates a great ambient light, as well as providing focus below the fitting.

**IP40**

### SPECIFICATIONS

#### Material Specifications

<b>Material</b>	1.0mm Aluminium Housing, with Opal Acrylic Diffuser
<b>Colour</b>	Powdercoat, Black or White
<b>Ingress Protection</b>	IP44
<b>Dimensions</b>	1405mm(L) x 62mm(W) x 82mm(D)
<b>Suspension Length</b>	1200mm
<b>Warranty</b>	5 Year Replacement

#### Electrical Specifications

<b>Power Supply</b>	Osram LED Driver, Non-Dimmable
<b>Input Voltage</b>	240V

#### Optic Specifications

<b>Light Source</b>	38W Direct/ 19W Indirect, Epistar SMD 5630
<b>Nominal Lumens</b>	5,865lm (3910lm Down / 1955lm Up)
<b>CRI</b>	80Ra
<b>Beam Angle</b>	120°
<b>Colour Deviation</b>	SDCM ≤ 3
<b>Rated Lifetime (L70B20)</b>	50,000 Hrs

### VARIATIONS

<b>LC8203</b>	ASTON Linear Pendant, 38W Direct/ 19W Indirect, Black, Non-Dim, 3000K
<b>LC8204</b>	ASTON Linear Pendant, 38W Direct/ 19W Indirect, White, Non-Dim, 3000K
<b>LC8205</b>	ASTON Linear Pendant, 38W Direct/ 19W Indirect, Black, Non-Dim, 4000K
<b>LC8206</b>	ASTON Linear Pendant, 38W Direct/ 19W Indirect, White, Non-Dim, 4000K