Classic Series
Proven. Quality. Customisable

ASTON 67W
Direct/Indirect Pendant 1685mm



The ASTON Linear Series are a sleek, modern style perfect for commercial architecture. With a thin profile, this style is available in suspended, surface mounted and recessed.

The ASTON 67W Linear Direct/Indirect Pendant 1685mm is ideal for offices with higher ceilings. It creates a great ambient light, as well as providing focus below the fitting.



IP40

SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Opal Acrylic Diffuser
Colour	Powdercoat, Black or White
Ingress Protection	IP44
Dimensions	1685mm(L) x 62mm(W) x 82mm(D)
Suspension Length	1200mm
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram LED Driver, Non-Dimmable
Input Voltage	240V

Optic Specifications

Light Source	45W Direct/ 22W Indirect, Epistar SMD 5630
Nominal Lumens	6910lm
CRI	80Ra
Beam Angle	120°
Colour Deviation	SDCM ≤ 3
Rated Lifetime (L70B20)	50,000 Hrs

VARIATIONS

LC8223	ASTON Linear Pendant, 45W Direct/ 22W Indirect, Black, Non-Dim, 3000K
LC8224	ASTON Linear Pendant, 45W Direct/ 22W Indirect, White, Non-Dim, 3000K
LC8225	ASTON Linear Pendant, 45W Direct/ 22W Indirect, Black, Non-Dim, 4000K
LC8226	ASTON Linear Pendant, 45W Direct/ 22W Indirect, White, Non-Dim, 4000K

Product design and technical data may be subject to change without prior notice.
Generated 29th Mar 2024 - © Decrolux

CE E582