

Classic Series

Proven. Quality. Customisable

ASTON MK-II 15W Recessed Profile

The ASTON MK-II Linear Series are a sleek, modern style perfect for commercial architecture. Depending on the height and type of ceiling, you can choose to either surface mount or suspend the linear profiles. A third, slightly less common mounting method, is to recess the lights directly into the ceiling.

The ASTON 15W Linear Recessed Profile is used for modern areas to achieve a minimal appearance. Smooth lines give a subtle, crisp look. The MK-II version features a low-glare, prismatic diffuser.



IP44



SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Opal Acrylic Diffuser
Finish	White or Black Powdercoat
Ingress Protection	IP44
Dimensions	579mm(L) x 65mm(W) x 88mm(D)
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	BOKE LED Driver
Input Voltage	240V

Optic Specifications

Light Source	Samsung 2835 SMD
LED Wattage	27W/m
Nominal Lumens	1,635lm
Efficacy	109lm/W
CRI	> 80Ra
UGR	UGR <19
Beam Angle	85°
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	> 54,000 Hrs



VARIATIONS

LC8423B	ASTON MK-II 15W Recessed 561mm, Black, 85°, Non-Dim, 3000K
LC8423BD	ASTON MK-II 15W Recessed 561mm, Black, 85°, DALI, 3000K
LC8423W	ASTON MK-II 15W Recessed 561mm, White, 85°, Non-Dim, 3000K
LC8423WD	ASTON MK-II 15W Recessed 561mm, White, 85°, DALI, 3000K
LC8424B	ASTON MK-II 15W Recessed 561mm, Black, 85°, Non-Dim, 4000K
LC8424BD	ASTON MK-II 15W Recessed 561mm, Black, 85°, DALI, 4000K
LC8424W	ASTON MK-II 15W Recessed 561mm, White, 85°, Non-Dim, 4000K
LC8424WD	ASTON MK-II 15W Recessed 561mm, White, 85°, DALI, 4000K