

# ASTON MK-II 22W

## Surface Mount Profile 841mm

**Classic Series**

Proven. Quality. Customisable

The ASTON 22W Surface Mount Linear Series are a sleek, modern style perfect for commercial architecture.

This sleek range is also available in suspended and recessed.

If you are building, we offer a lighting design service. Simply send us your (floor plan) and let us know your desired outcome. Our design team can make a recommendation for you.

**IP44**

### SPECIFICATIONS

#### Material Specifications

Material	1.0mm Aluminium Housing, with Prismatic Diffuser
Colour	Powdercoat, Black or White
Dimensions	841mm(L) x 65mm(W) x 88mm(D)
Ingress Protection	IP44
Warranty	5 Year Replacement

#### Electrical Specifications

Power Supply	Osram 900mA Integrated Driver, Non-Dim
Options	0-10V Dim/CRI90
Input Voltage	240V

#### Optic Specifications

Light Source	Samsung 2835 SMD
LED Wattage	27W/m
Nominal Lumens	2240lm
CRI	80Ra
Beam Angle	85°
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	> 54,000 Hrs

### VARIATIONS

<b>LC8483B</b>	ASTON MK-II 22W Surface Mount Profile, Black, 85°, Non-Dim, 3000K
<b>LC8483W</b>	ASTON MK-II 22W Surface Mount Profile, White, 85°, Non-Dim, 3000K
<b>LC8484B</b>	ASTON MK-II 22W Surface Mount Profile, Black, 85°, Non-Dim, 4000K
<b>LC8484W</b>	ASTON MK-II 22W Surface Mount Profile, White, 85°, Non-Dim, 4000K

