

ASTON MK-II 22W

Suspended Profile 841mm

The ASTON 22W Surface Mount Linear Series are a sleek, modern style perfect for commercial architecture.

This sleek range is also available in suspended and recessed.

If you are building, we offer a lighting design service. Simply send us your (floor plan) and let us know your desired outcome. Our design team can make a recommendation for you.







SPECIFICATIONS

Material Specifications

Material 1.0mm Aluminium Housing, with Prismatic

Diffuser

ColourPowdercoat, Black or WhiteDimensions $841 \text{mm}(L) \times 65 \text{mm}(W) \times 88 \text{mm}(D)$

Ingress Protection IP44

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Osram 900mA Integrated Driver, Non-Dim

Options 0-10V Dim/CRI90

Input Voltage 240V

Optic Specifications

Light Source Samsung 2835 SMD

 LED Wattage
 27W/m

 Nominal Lumens
 2240lm

 CRI
 80Ra

 Beam Angle
 85°

 Colour Deviation
 SDCM ≤ 3

 Reported L70 (Hours)
 > 54,000 Hrs

VARIATIONS

LC8493B ASTON MK-II 22W Suspended, Black, 85°, Non-Dim, 3000K LC8493BD ASTON MK-II 22W Suspended, Black, 85°, DALI, 3000K ASTON MK-II 22W Suspended, Silver, 85°, Non-Dim, 3000K LC8493S LC8493SD ASTON MK-II 22W Suspended, Silver, 85°, DALI, 3000K ASTON MK-II 22W Suspended, White, 85°, Non-Dim, 3000K LC8493W LC8493WD ASTON MK-II 22W Suspended, White, 85°, DALI, 3000K ASTON MK-II 22W Suspended, Black, 85°, Non-Dim, 4000K LC8494B ASTON MK-II 22W Suspended, Black, 85°, DALI, 4000K LC8494BD LC8494S ASTON MK-II 22W Suspended, Silver, 85°, Non-Dim, 4000K ASTON MK-II 22W Suspended, Silver, 85°, DALI, 4000K LC8494SD LC8494W ASTON MK-II 22W Suspended, White, 85°, Non-Dim, 4000K LC8494WD ASTON MK-II 22W Suspended, White, 85°, DALI, 4000K







Classic Series Proven. Quality. Customisable

