

ASTON MK-II 30W

Recessed Profile 1121mm

Classic Series

Proven. Quality. Customisable

The ASTON MK-II Linear Series are a sleek, modern style perfect for commercial architecture. Depending on the height and type of ceiling, you can choose to either surface mount or suspend the linear profiles. A third, slightly less common mounting method, is to recess the lights directly into the ceiling.

The ASTON 30W Linear Recessed Profile is used for modern areas to achieve a minimal appearance. Smooth lines give a subtle, crisp look. The MK-II version features a low-glare, prismatic diffuser.



IP44



SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Opal Acrylic Diffuser
Finish	Powdercoat (Black, White or Silver)
Ingress Protection	IP44
Dimensions	1121mm(L) x 79mm(W) x 40mm(D)
Cutout	71mm(W)
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram LED Integrated Driver
Dimming	Non-Dim, 0-10V or DALI
Input Voltage	240V
System Watts	27W/m

Optic Specifications

Light Source	Samsung 2835 SMD
Efficacy	84lm/W
CRI	> 80Ra
Beam Angle	85°
UGR	UGR <19
Colour Deviation	SDCM ≤ 3



VARIATIONS

LC8523B	ASTON MK-II 30W Recessed 1121mm, Black, 85°, Non-Dim, 3000K
LC8523BD	ASTON MK-II 30W Recessed 1121mm, Black, 85°, DALI, 3000K
LC8523W	ASTON MK-II 30W Recessed 1121mm, White, 85°, Non-Dim, 3000K
LC8523WD	ASTON MK-II 30W Recessed 1121mm, White, 85°, DALI, 3000K
LC8523S	ASTON MK-II 30W Recessed 1121mm, Silver, 85°, Non-Dim, 3000K
LC8523SD	ASTON MK-II 30W Recessed 1121mm, Silver, 85°, DALI, 3000K
LC8524B	ASTON MK-II 30W Recessed 1121mm, Black, 85°, Non-Dim, 4000K
LC8524BD	ASTON MK-II 30W Recessed 1121mm, Black, 85°, DALI, 4000K
LC8524W	ASTON MK-II 30W Recessed 1121mm, White, 85°, Non-Dim, 4000K
LC8524WD	ASTON MK-II 30W Recessed 1121mm, White, 85°, DALI, 4000K
LC8524S	ASTON MK-II 30W Recessed 1121mm, Silver, 85°, Non-Dim, 4000K

LC8524S

ASTON MK-II 30W Recessed 1121mm, Silver, 85°, DALI, 4000K

Classic Series

Proven. Quality. Customisable