

ASTON MK-II 30W

Surface Mount Profile

The ASTON MK-II 30W Linear Surface Mount Profile is a sleek, modern style perfect for commercial architecture. Architectural linear suspensions bring clean lines to commercial interiors. Our sleek, stylish LED linear suspensions offer highly effective and efficient lighting solutions for schools, libraries, office spaces, and retail outlets. This style is also available in suspended, wall and recessed.







SPECIFICATIONS

Material Specifications

Material 1.0mm Aluminium Housing, with Prismatic

Diffuser

Finish Powdercoat

Dimensions 1133mm(L) x 65mm(W) x 88mm(D)

Ingress Protection IP44

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Osram 900mA Integrated LED Driver, Non-Dim

Options 0-10V Dim/ CRI90

Input Voltage 240V

Optic Specifications

Light Source Samsung 2835 SMD

27W/m **LED** Wattage **Delivered Lumens** 3,060lm 102lm/W **Efficacy** CRI 80Ra **UGR** UGR <19 85° **Beam Angle Colour Deviation** SDCM ≤ 3 Reported L70 (Hours) > 54,000 Hrs

VARIATIONS

LC8533B ASTON MK-II 30W Surface Mount, Black, 85°, Non-Dim, 3000K ASTON MK-II 30W Surface Mount, Black, 85°, DALI, 3000K LC8533BD LC8533W ASTON MK-II 30W Surface Mount, White, 85°, Non-Dim, 3000K ASTON MK-II 30W Surface Mount, White, 85°, DALI, 3000K LC8533WD LC8534B ASTON MK-II 30W Surface Mount, Black, 85°, Non-Dim, 4000K ASTON MK-II 30W Surface Mount, Black, 85°, DALI, 4000K LC8534BD ASTON MK-II 30W Surface Mount, White, 85°, Non-Dim, 4000K LC8534W ASTON MK-II 30W Surface Mount, White, 85°, DALI, 4000K LC8534WD



