

Classic Series

Proven. Quality. Customisable

ASTON MK-II 30W

Surface Mount Profile 1121mm

The ASTON MK-II 30W Linear Surface Mount Profile is a sleek, modern style perfect for commercial architecture. Architectural linear suspensions bring clean lines to commercial interiors. Our sleek, stylish LED linear suspensions offer highly effective and efficient lighting solutions for schools, libraries, office spaces, and retail outlets. This style is also available in suspended, wall and recessed.



SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Prismatic Diffuser
Finish	Powdercoat
Dimensions	1121mm(L) x 65mm(W) x 88mm(D)
Ingress Protection	IP44
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram 900mA Integrated LED Driver, Non-Dim
Options	0-10V Dim/ CRI90
Input Voltage	240V

Optic Specifications

Light Source	Samsung 2835 SMD
LED Wattage	27W/m
Delivered Lumens	3,060lm
Efficacy	102lm/W
CRI	80Ra
UGR	UGR <19
Beam Angle	85°
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	> 54,000 Hrs

VARIATIONS

LC8533B	ASTON MK-II 30W Surface Mount, Black, 85°, Non-Dim, 3000K
LC8533BD	ASTON MK-II 30W Surface Mount, Black, 85°, DALI, 3000K
LC8533S	ASTON MK-II 30W Surface Mount, Silver, 85°, Non-Dim, 3000K
LC8533SD	ASTON MK-II 30W Surface Mount, Silver, 85°, DALI, 3000K
LC8533W	ASTON MK-II 30W Surface Mount, White, 85°, Non-Dim, 3000K
LC8533WD	ASTON MK-II 30W Surface Mount, White, 85°, DALI, 3000K
LC8534B	ASTON MK-II 30W Surface Mount, Black, 85°, Non-Dim, 4000K
LC8534BD	ASTON MK-II 30W Surface Mount, Black, 85°, DALI, 4000K
LC8534S	ASTON MK-II 30W Surface Mount, Silver, 85°, Non-Dim, 4000K
LC8534SD	ASTON MK-II 30W Surface Mount, Silver, 85°, DALI, 4000K
LC8534W	ASTON MK-II 30W Surface Mount, White, 85°, Non-Dim, 4000K
LC8534WD	ASTON MK-II 30W Surface Mount, White, 85°, DALI, 4000K

Classic Series

Proven. Quality. Customisable