

ASTON MK-II 30W

Surface Mount Profile 1121mm

The ASTON MK-II 30W Linear Surface Mount Profile is a sleek, modern style perfect for commercial architecture. Architectural linear suspensions bring clean lines to commercial interiors. Our sleek, stylish LED linear suspensions offer highly effective and efficient lighting solutions for schools, libraries, office spaces, and retail outlets. This style is also available in suspended, wall and recessed.







SPECIFICATIONS

Material Specifications

Material 1.0mm Aluminium Housing, with Prismatic

Diffuser

Finish Powdercoat

Dimensions 1121mm(L) x 65mm(W) x 88mm(D)

Ingress Protection IP44

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Osram 900mA Integrated LED Driver, Non-Dim

Options 0-10V Dim/ CRI90

Input Voltage 240V

Optic Specifications

Light Source Samsung 2835 SMD

LED Wattage 27W/m **Delivered Lumens** 3,060lm **Efficacy** 102lm/W CRI 80Ra **UGR** UGR <19 **Beam Angle** 85° **Colour Deviation** SDCM ≤ 3 Reported L70 (Hours) > 54,000 Hrs

VARIATIONS

LC8533B ASTON MK-II 30W Surface Mount, Black, 85°, Non-Dim, 3000K LC8533BD ASTON MK-II 30W Surface Mount, Black, 85°, DALI, 3000K LC8533S ASTON MK-II 30W Surface Mount, Silver, 85°, Non-Dim, 3000K ASTON MK-II 30W Surface Mount, Silver, 85°, DALI, 3000K LC8533SD LC8533W ASTON MK-II 30W Surface Mount, White, 85°, Non-Dim, 3000K ASTON MK-II 30W Surface Mount, White, 85°, DALI, 3000K LC8533WD ASTON MK-II 30W Surface Mount, Black, 85°, Non-Dim, 4000K LC8534B ASTON MK-II 30W Surface Mount, Black, 85°, DALI, 4000K LC8534BD LC8534S ASTON MK-II 30W Surface Mount, Silver, 85°, Non-Dim, 4000K ASTON MK-II 30W Surface Mount, Silver, 85°, DALI, 4000K LC8534SD LC8534W ASTON MK-II 30W Surface Mount, White, 85°, Non-Dim, 4000K LC8534WD ASTON MK-II 30W Surface Mount, White, 85°, DALI, 4000K









Classic Series Proven. Quality. Customisable

