

ASTON MK-II 30W

Suspended Profile

Classic Series

Proven. Quality. Customisable

The ASTON MK-II Linear Pendant Series are a sleek, modern style perfect for commercial architecture. Architectural linear suspensions bring clean lines to commercial interiors. Our sleek, stylish LED linear suspensions offer highly effective and efficient lighting solutions for schools, libraries, office spaces, and retail outlets. This style is also available in suspended, surface mounted and recessed. The MK-II version features a low-glare, prismatic diffuser.



SPECIFICATIONS

Material Specifications


Material	1.0mm Aluminium Housing, with Prismatic Diffuser
Finish	Powdercoat
Dimensions	1121mm(L) x 65mm(W) x 88mm(D)
Suspension Length	2000mm (Max)
Ingress Protection	IP44
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram 900mA Integrated LED Driver, Non-Dim
Options	DALI or 0-10V Dimmable
LED Wattage	27W/m
Input Voltage	240V

Optic Specifications

Light Source	Samsung 2835 SMD
Efficacy	>100lm/W
CRI	>80Ra
UGR	UGR <19
Beam Angle	85°
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	> 54,000 Hrs



VARIATIONS

LC8553W	ASTON MK-II 30W Suspended, White, 85°, Non-Dim, 3000K
LC8553WD	ASTON MK-II 30W Suspended, White, 85°, DALI, 3000K
LC8553B	ASTON MK-II 30W Suspended, Black, 85°, Non-Dim, 3000K
LC8553BD	ASTON MK-II 30W Suspended, Black, 85°, DALI, 3000K
LC8554W	ASTON MK-II 30W Suspended, White, 85°, Non-Dim, 4000K
LC8554WD	ASTON MK-II 30W Suspended, White, 85°, DALI, 4000K
LC8554B	ASTON MK-II 30W Suspended, Black, 85°, Non-Dim, 4000K
LC8554BD	ASTON MK-II 30W Suspended, Black, 85°, DALI, 4000K
LC8554S	ASTON MK-II 30W Suspended, Silver, 85°, Non-Dim, 4000K
LC8554SD	ASTON MK-II 30W Suspended, Silver, 85°, DALI, 4000K
LC8554WZ	ASTON MK-II 30W Suspended, White, 85°, 0-10V Dim, 4000K