

ASTON MK-II 30W

Suspended Profile

The ASTON MK-II Linear Pendant Series are a sleek, modern style perfect for commercial architecture. Architectural linear suspensions bring clean lines to commercial interiors. Our sleek, stylish LED linear suspensions offer highly effective and efficient lighting solutions for schools, libraries, office spaces, and retail outlets. This style is also available in suspended, surface mounted and recessed. The MK-II features a low-glare, prismatic diffuser.







SPECIFICATIONS

Material Specifications

Material 1.0mm Aluminium Housing, with Prismatic

Diffuser

Finish Powdercoat

Dimensions 1131mm(L) x 65mm(W) x 88mm(D)

Suspension Length 2000mm (Max)

Ingress Protection IP44

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Osram 900mA Integrated LED Driver

Input Voltage 240V

Optic Specifications

Light Source Samsung 2835 SMD

LED Wattage 27W/m **Delivered Lumens** 3,060lm **Efficacy** 102lm/W CRI > 80Ra **UGR** UGR <19 85° **Beam Angle Colour Deviation** SDCM ≤ 3 Reported L70 (Hours) > 54,000 Hrs

VARIATIONS

LC8553W	ASTON MK-II 30W Suspended, White, 85° , Non-Dim, 3000K
LC8553WD	ASTON MK-II 30W Suspended, White, 85°, DALI, 3000K
LC8553B	ASTON MK-II 30W Suspended, Black, 85° , Non-Dim, 3000K
LC8553BD	ASTON MK-II 30W Suspended, Black, 85°, DALI, 3000K
LC8554W	ASTON MK-II 30W Suspended, White, 85° , Non-Dim, 4000K
LC8554WD	ASTON MK-II 30W Suspended, White, 85°, DALI, 4000K
LC8554B	ASTON MK-II 30W Suspended, Black, 85° , Non-Dim, 4000K
LC8554BD	ASTON MK-II 30W Suspended, Black, 85°, DALI, 4000K
LC8554S	ASTON MK-II 30W Suspended, Silver, 85°, Non-Dim, 4000K



