

ASTON MK-II 38W


Recessed Profile

Classic Series

Proven. Quality. Customisable

The ASTON MK-II 38W Recessed Profiles are a sleek, modern style perfect for commercial architecture. Architectural linear suspensions bring clean lines to commercial interiors. Our sleek, stylish LED linear suspensions offer highly effective and efficient lighting solutions for schools, libraries, office spaces, and retail outlets. This style is also available in suspended, surface or wall-mounted.

The MK-II Features a low-glare, prismatic diffuser.



IP44



SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Prismatic Diffuser
Finish	Powdercoat
Dimensions	1411mm(L) x 65mm(W) x 88mm(D)
Ingress Protection	IP44
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram 900mA Integrated LED Driver
Input Voltage	240V

Optic Specifications

Light Source	Samsung 2835 SMD
LED Wattage	27W/m
CRI	> 80Ra
Beam Angle	85°
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	> 54,000 Hrs

VARIATIONS

LC8583W	ASTON MK-II 38W Recessed, White, 85°, Non-Dim, 3000K
LC8583WD	ASTON MK-II 38W Recessed, White, 85°, DALI, 3000K
LC8583B	ASTON MK-II 38W Recessed, Black, 85°, Non-Dim, 3000K
LC8583BD	ASTON MK-II 38W Recessed, Black, 85°, DALI, 3000K
LC8584W	ASTON MK-II 38W Recessed, White, 85°, Non-Dim, 4000K
LC8584WD	ASTON MK-II 38W Recessed, White, 85°, DALI, 4000K
LC8584B	ASTON MK-II 38W Recessed, Black, 85°, Non-Dim, 4000K
LC8584BD	ASTON MK-II 38W Recessed, Black, 85°, DALI, 4000K

