

Classic Series

Proven. Quality. Customisable

ASTON MK-II 38W

Surface Mount Profile

The ASTON MK-II 38W Linear Surface Mount Profiles are a sleek, modern style perfect for commercial architecture. Architectural linear suspensions bring clean lines to commercial interiors. Our sleek, stylish LED linear suspensions offer highly effective and efficient lighting solutions for schools, libraries, office spaces, and retail outlets. This style is also available in suspended, wall-mounted and recessed.

The MK-II Features a low-glare, prismatic diffuser.



SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Prismatic Diffuser
Finish	Powdercoat
Dimensions	1411mm(L) x 65mm(W) x 88mm(D)
Ingress Protection	IP44
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram 900mA Integrated LED Driver
Input Voltage	240V

Optic Specifications

Light Source	Samsung 2835 SMD
LED Wattage	27W/m
CRI	> 80Ra
Beam Angle	85°
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	> 54,000 Hrs

VARIATIONS

LC8593W	ASTON MK-II 38W Surface Mount, White, 85°, Non-Dim, 3000K
LC8593WD	ASTON MK-II 38W Surface Mount, White, 85°, DALI, 3000K
LC8593B	ASTON MK-II 38W Surface Mount, Black, 85°, Non-Dim, 3000K
LC8593BD	ASTON MK-II 38W Surface Mount, Black, 85°, DALI, 3000K
LC8594W	ASTON MK-II 38W Surface Mount, White, 85°, Non-Dim, 4000K
LC8594WD	ASTON MK-II 38W Surface Mount, White, 85°, DALI, 4000K
LC8594B	ASTON MK-II 38W Surface Mount, Black, 85°, Non-Dim, 4000K
LC8594BD	ASTON MK-II 38W Surface Mount, Black, 85°, DALI, 4000K