

ASTON MK-II 38W

Surface Mount Profile 1401mm

The ASTON MK-II 38W Linear Surface Mount Profiles are a sleek, modern style perfect for commercial architecture. Architectural linear suspensions bring clean lines to commercial interiors. Our sleek, stylish LED linear suspensions offer highly effective and efficient lighting solutions for schools, libraries, office spaces, and retail outlets. This style is also available in suspended, wall-mounted and recessed.

The MK-II Features a low-glare, prismatic diffuser.







SPECIFICATIONS

Material Specifications

Material 1.0mm Aluminium Housing, with Prismatic

Diffuser

Finish Powdercoat

Dimensions 1401mm(L) x 65mm(W) x 88mm(D)

Ingress Protection IP44

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Osram 900mA Integrated LED Driver

Input Voltage 240V

Optic Specifications

Light Source Samsung 2835 SMD

 LED Wattage
 27W/m

 CRI
 > 80Ra

 Beam Angle
 85°

 Colour Deviation
 SDCM ≤ 3

 Reported L70 (Hours)
 > 54,000 Hrs

VARIATIONS

LC8593B ASTON MK-II 38W Surface Mount, Black, 85°, Non-Dim, 3000K LC8593BD ASTON MK-II 38W Surface Mount, Black, 85°, DALI, 3000K ASTON MK-II 38W Surface Mount, Silver, 85°, Non-Dim, 3000K LC8593S ASTON MK-II 38W Surface Mount, Silver, 85°, DALI, 3000K LC8593SD LC8593W ASTON MK-II 38W Surface Mount, White, 85°, Non-Dim, 3000K ASTON MK-II 38W Surface Mount, White, 85°, DALI, 3000K LC8593WD LC8594B ASTON MK-II 38W Surface Mount, Black, 85°, Non-Dim, 4000K LC8594BD ASTON MK-II 38W Surface Mount, Black, 85°, DALI, 4000K ASTON MK-II 38W Surface Mount, Silver, 85°, Non-Dim, 4000K LC8594S LC8594SD ASTON MK-II 38W Surface Mount, Silver, 85°, DALI, 4000K ASTON MK-II 38W Surface Mount, White, 85°, Non-Dim, 4000K LC8594W LC8594WD ASTON MK-II 38W Surface Mount, White, 85°, DALI, 4000K ASTON MK-II 38W Wall Mount, White, 85°, Non-Dim, 4000K I C8594W-

Classic Series
Proven. Quality. Customisable

