

ASTON MK-II 45W

Surface Mount Profile

The ASTON MK-II 45W Surface Mount Linear Profiles are a sleek, modern style perfect for commercial architecture. Architectural linear suspensions bring clean lines to commercial interiors. Our sleek, stylish LED linear suspensions offer highly effective and efficient lighting solutions for schools, libraries, office spaces, and retail outlets. This style is also available in suspended, wall-mounted and recessed.

The MK-II features a low-glare, prismatic diffuser.







SPECIFICATIONS

Material Specifications

Material 1.0mm Aluminium Housing, with Prismatic

Diffuser

Finish Powdercoat

Dimensions 1691mm(L) x 65mm(W) x 88mm(D)

Ingress Protection IP44

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Osram 900mA Integrated LED Driver

Input Voltage 240V

Optic Specifications

Light Source Samsung 2835 SMD

 LED Wattage
 27W/m

 CRI
 > 80Ra

 Beam Angle
 85°

 Colour Deviation
 SDCM ≤ 3

 Reported L70 (Hours)
 > 54,000 Hrs

VARIATIONS

LC8643W ASTON MK-II 45W Surface Mount, White, 85°, Non-Dim, 3000K ASTON MK-II 45W Surface Mount, White, 85°, DALI, 3000K LC8643WD ASTON MK-II 45W Surface Mount, Black, 85°, Non-Dim, 3000K LC8643B ASTON MK-II 45W Surface Mount, Black, 85°, DALI, 3000K LC8643BD ASTON MK-II 45W Surface Mount, White, 85°, Non-Dim, 4000K LC8644W ASTON MK-II 45W Surface Mount, White, 85°, DALI, 4000K LC8644WD LC8644B ASTON MK-II 45W Surface Mount, Black, 85°, Non-Dim, 4000K ASTON MK-II 45W Surface Mount, Black, 85°, DALI, 4000K LC8644BD LC8644S ASTON MK-II 45W Surface Mount, Silver, 85°, Non-Dim, 4000K



