decrolux Illuminating spaces. Inspiring growth.

ASTON MK-II 45W Surface Mount Profile 1681mm

The ASTON MK-II 45W Surface Mount Linear Profiles are a sleek, modern style perfect for commercial architecture. Architectural linear suspensions bring clean lines to commercial interiors. Our sleek, stylish LED linear suspensions offer highly effective and efficient lighting solutions for schools, libraries, office spaces, and retail outlets. This style is also available in suspended, wall-mounted and recessed.

The MK-II features a low-glare, prismatic diffuser.



SPECIFICATIONS

Material Specifications

Materia	

Finish
Dimensions
Ingress Protection
Warranty

1.0mm Aluminium Housing, with Prismatic Diffuser Powdercoat 1681mm(L) x 65mm(W) x 88mm(D) IP44 5 Year Replacement

Electrical Specifications

Power Supply Input Voltage Osram 900mA Integrated LED Driver 240V

Optic Specifications

Light Source LED Wattage CRI Beam Angle Colour Deviation Reported L70 (Hours) Samsung 2835 SMD 27W/m > 80Ra 85°

SDCM ≤ 3

> 54,000 Hrs

. ,

VARIATIONS

LC8643B	ASTON MK-II 45W Surface Mount, Black, 85°, Non-Dim, 3000K
LC8643BD	ASTON MK-II 45W Surface Mount, Black, 85°, DALI, 3000K
LC8643S	ASTON MK-II 45W Surface Mount, Silver, 85°, Non-Dim, 3000K
LC8643SD	ASTON MK-II 45W Surface Mount, Silver, 85°, DALI, 3000K
LC8643W	ASTON MK-II 45W Surface Mount, White, 85°, Non-Dim, 3000K
LC8643WD	ASTON MK-II 45W Surface Mount, White, 85°, DALI, 3000K
LC8644B	ASTON MK-II 45W Surface Mount, Black, 85°, Non-Dim, 4000K
LC8644BD	ASTON MK-II 45W Surface Mount, Black, 85°, DALI, 4000K
LC8644S	ASTON MK-II 45W Surface Mount, Silver, 85°, Non-Dim, 4000K
LC8644SD	ASTON MK-II 45W Surface Mount, Silver, 85°, DALI, 4000K
LC8644W	ASTON MK-II 45W Surface Mount, White, 85°, Non-Dim, 4000K
LC8644WD	ASTON MK-II 45W Surface Mount, White, 85°, DALI, 4000K
LC8644W- WM	ASTON MKII-45W Wall Mount, White, 85°, Non-Dim, 4000K





