


ASTON MK-II 52W

Recessed Profile 1961mm

Classic Series

Proven. Quality. Customisable

The ASTON Linear Series are a sleek, modern style perfect for commercial architecture. With a thin profile, this style is available in suspended, surface mounted and recessed. ASTON 52W Linear Recessed 1961mm is a simple, modular fitting which can be connected together. 5 Year Warranty.



IP44



SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Opal Acrylic Diffuser
Colour	Powdercoat (Black, White or Silver)
Ingress Protection	IP44
Dimensions	1961mm(L) x 79mm(W) x 40mm(D)
Cutout	71mm(W)
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram LED Integrated Driver
Dimming	Non-Dim, 0-10V or DALI
Input Voltage	240V
LED Wattage	27W/m

Optic Specifications

Light Source	Samsung 2835 SMD
Efficacy	84lm/W
CRI	80Ra
Beam Angle	85°
UGR	UGR <19
Colour Deviation	SDCM ≤ 3

VARIATIONS

LC8663B	ASTON MK-II 52W Recessed Profile, 1961mm, Black, 85°, Non-Dim, 3000K
LC8663BD	ASTON MK-II 52W Recessed Profile, 1961mm, Black, 85°, DALI, 3000K
LC8663W	ASTON MK-II 52W Recessed Profile, 1961mm, White, 85°, Non-Dim, 3000K
LC8663WD	ASTON MK-II 52W Recessed Profile, 1961mm, White, 85°, DALI, 3000K
LC8664B	ASTON MK-II 52W Recessed Profile, 1961mm, Black, 85°, Non-Dim, 4000K
LC8664BD	ASTON MK-II 52W Recessed Profile, 1961mm, Black, 85°, DALI, 4000K
LC8664W	ASTON MK-II 52W Recessed Profile, 1961mm, White, 85°, Non-Dim, 4000K
LC8664WD	ASTON MK-II 52W Recessed Profile, 1961mm, White, 85°, DALI, 4000K

