decrolux Illuminating spaces. Inspiring growth.

1300 827 284 www.decrolux.com.au

ASTON MK-II 52W Suspended Profile 1961mm

The ASTON MK-II Linear Pendant Series are a sleek, modern style perfect for commercial architecture. Architectural linear suspensions bring clean lines to commercial interiors. Our sleek, stylish LED linear suspensions offer highly effective and efficient lighting solutions for schools, libraries, office spaces, and retail outlets. This style is also available in suspended, surface mounted and recessed. The MK-II version features a low-glare, prismatic diffuser.

Diffuser

IP44

27W/m

240V

Powdercoat

2000mm (Max)

5 Year Replacement

DALI or 0-10V Dimmable

1.0mm Aluminium Housing, with Prismatic

Osram 900mA Integrated LED Driver, Non-Dim

1961mm(L) x 65mm(W) x 88mm(D)

IP44

SPECIFICATIONS

Material Specifications

Material

Finish Dimensions Suspension Length Ingress Protection Warranty

Electrical Specifications

Power Supply Options LED Wattage Input Voltage

Optic Specifications

Light Source	Samsung 2835 SMD
Efficacy	>100lm/W
CRI	> 80Ra
UGR	UGR <19
Beam Angle	85°
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	> 54,000 Hrs

VARIATIONS

LC8683B	ASTON MK-II 52W Suspended, Black, 85°, Non-Dim, 3000K
LC8683BD	ASTON MK-II 52W Suspended, Black, 85°, DALI, 3000K
LC8683W	ASTON MK-II 52W Suspended, White, 85°, Non-Dim, 3000K
LC8683WD	ASTON MK-II 52W Suspended, White, 85°, DALI, 3000K
LC8684B	ASTON MK-II 52W Suspended, Black, 85°, Non-Dim, 4000K
LC8684BD	ASTON MK-II 52W Suspended, Black, 85°, DALI, 4000K
LC8684W	ASTON MK-II 52W Suspended, White, 85°, Non-Dim, 4000K
LC8684WD	ASTON MK-II 52W Suspended, White, 85°, DALI, 4000K
LC8684WZ	ASTON MK-II 52W Suspended, White, 85°, 0-10V Dim, 4000K
LC8684S	ASTON MK-II 52W Suspended, Silver, 85°, Non-Dim, 4000K
LC8684SD	ASTON MK-II 52W Suspended, Silver, 85°, DALI, 4000K









1300 827 284 www.decrolux.com.au

Classic Series Proven. Quality. Customisable

