

Classic Series

Proven. Quality. Customisable

ASTON MK-II 57W

Suspended Direct/Indirect Pendant 1401mm

The ASTON MK-II 57W Linear Series are a sleek, modern style perfect for commercial architecture. With a thin profile, this style is available in suspended, surface mounted and recessed.

The ASTON 57W Linear Direct/Indirect Pendant 1405mm is ideal for offices with higher ceilings. It creates a great ambient light, as well as providing focus below the fitting.



SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Opal Acrylic Diffuser
Colour	Powdercoat, Black or White
Ingress Protection	IP44
Dimensions	1401mm(L) x 65mm(W) x 88mm(D)
Suspension Length	2000mm
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram LED Driver, Non-Dimmable
Input Voltage	240V

Optic Specifications

Light Source	38W Direct/ 19W Indirect, Epistar SMD 5630
Nominal Lumens	5,865lm (3910lm Down / 1955lm Up)
CRI	80Ra
Beam Angle	85°
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	> 54,000 Hrs

VARIATIONS

LC8693B	ASTON MK-II 57W Suspended, 38W Direct/ 19W Indirect, Black, 85°, Non-Dim, 3000K
LC8693BD	ASTON MK-II 57W Suspended, 38W Direct/ 19W Indirect, Black, 85°, DALI, 3000K
LC8693W	ASTON MK-II 57W Suspended, 38W Direct/ 19W Indirect, White, 85°, Non-Dim, 3000K
LC8693WD	ASTON MK-II 57W Suspended, 38W Direct/ 19W Indirect, White, 85°, DALI, 3000K
LC8694B	ASTON MK-II 57W Suspended, 38W Direct/ 19W Indirect, Black, 85°, Non-Dim, 4000K
LC8694BD	ASTON MK-II 57W Suspended, 38W Direct/ 19W Indirect, Black, 85°, DALI, 4000K
LC8694W	ASTON MK-II 57W Suspended, 38W Direct/ 19W Indirect, White, 85°, Non-Dim, 4000K
LC8694WD	ASTON MK-II 57W Suspended, 38W Direct/ 19W Indirect, White, 85°, DALI, 4000K

Classic Series

Proven. Quality. Customisable