

Classic Series

Proven. Quality. Customisable

ASTON MK-II 60W

Recessed Profile

The ASTON MK-II 60W Recessed Linear Profiles are a sleek, modern style perfect for commercial architecture. Architectural linear lighting bring clean lines to commercial interiors. Our sleek, stylish LED linear recessed profiles offer highly effective and efficient lighting solutions for schools, libraries, office spaces, and retail outlets. This style is also available in suspended, wall-mounted and surface mount.

The MK-II features a low-glare, prismatic diffuser.



IP44

SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Prismatic Diffuser
Finish	Powdercoat (Black, White or Silver)
Dimensions	2241mm(L) x 79mm(W) x 40mm(D)
Ingress Protection	IP44
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram 900mA LED Driver
Options	DALI
Input Voltage	240V

Optic Specifications

Light Source	Samsung 2835 SMD
Efficacy	84lm/W
Delivered Lumens	5040lm
CRI	> 80Ra
Beam Angle	85°
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	> 54,000 Hrs

VARIATIONS

LC8703B	ASTON MK-II 60W Recessed, Black, 85°, DALI, 3000K
LC8703BD	ASTON MK-II 60W Recessed, Black, 85°, Non-Dim, 3000K
LC8703SD	ASTON MK-II 60W Recessed, Silver, 85°, DALI, 3000K
LC8703S	ASTON MK-II 60W Recessed, Silver, 85°, Non-Dim, 3000K
LC8703WD	ASTON MK-II 60W Recessed, White, 85°, DALI, 3000K
LC8703W	ASTON MK-II 60W Recessed, White, 85°, Non-Dim, 3000K
LC8704BD	ASTON MK-II 60W Recessed, Black, 85°, DALI, 4000K
LC8704B	ASTON MK-II 60W Recessed, Black, 85°, Non-Dim, 4000K
LC8704SD	ASTON MK-II 60W Recessed, Silver, 85°, DALI, 4000K
LC8704S	ASTON MK-II 60W Recessed, Silver, 85°, Non-Dim, 4000K
LC8704WD	ASTON MK-II 60W Recessed, White, 85°, DALI, 4000K
LC8704W	ASTON MK-II 60W Recessed, White, 85°, DALI, 4000K



Classic Series

Proven. Quality. Customisable