

ASTON MK-II 60W

Surface Mount Profile 2241mm

Classic Series

Proven. Quality. Customisable

The ASTON MK-II 60W Linear Surface Mount Profiles are a sleek, modern style perfect for commercial architecture. Architectural linear suspensions bring clean lines to commercial interiors. Our sleek, stylish LED linear suspensions offer highly effective and efficient lighting solutions for schools, libraries, office spaces, and retail outlets. This style is also available in suspended, surface mounted and recessed.



IP44



SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Prismatic Diffuser
Finish	Powdercoat
Dimensions	2241mm(L) x 65mm(W) x 88mm(D)
Ingress Protection	IP44
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram 900mA Integrated LED Driver
Input Voltage	240V

Optic Specifications

Light Source	Samsung 2835 SMD
LED Wattage	27W/m
CRI	> 80Ra
Beam Angle	85°
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	> 54,000 Hrs

VARIATIONS

LC8713B	ASTON MK-II 60W Surface Mount Profile, Black, 85°, Non-Dim, 3000K
LC8713BD	ASTON MK-II 60W Surface Mount Profile, Black, 85°, DALI, 3000K
LC8713W	ASTON MK-II 60W Surface Mount Profile, White, 85°, Non-Dim, 3000K
LC8713WD	ASTON MK-II 60W Surface Mount Profile, White, 85°, DALI, 3000K
LC8714B	ASTON MK-II 60W Surface Mount Profile, Black, 85°, Non-Dim, 4000K
LC8714BD	ASTON MK-II 60W Surface Mount Profile, Black, 85°, DALI, 4000K
LC8714W	ASTON MK-II 60W Surface Mount Profile, White, 85°, Non-Dim, 4000K
LC8714WD	ASTON MK-II 60W Surface Mount Profile, White, 85°, DALI, 4000K
LC8714S	ASTON MK-II 60W Surface Mount Profile, Silver, 85°, Non-Dim, 4000K

