

ASTON MK-II 67W

Suspended Direct/Indirect 1685mm

Classic Series

Proven. Quality. Customisable

The ASTON MK-II 67W Linear Series are a sleek, modern style perfect for commercial architecture. With a thin profile, this style is available in suspended, surface mounted and recessed.

The ASTON MK-II 67W Linear Direct/Indirect Pendant 1681mm is ideal for offices with higher ceilings. It creates a great ambient light, as well as providing focus below the fitting.



IP40



SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Opal Acrylic Diffuser
Colour	Powdercoat, Black or White
Ingress Protection	IP44
Dimensions	1681mm(L) x 65mm(W) x 82mm(D)
Suspension Length	2000mm
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram LED Driver
Input Voltage	240V

Optic Specifications

Light Source	45W Direct/ 22W Indirect, Epistar SMD 5630
Nominal Lumens	6910lm
CRI	> 80Ra
Beam Angle	85°
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	> 54,000 Hrs

VARIATIONS

LC8733B	ASTON MK-II 67W Suspended, 45W Direct/ 22W Indirect, Black, 85°, Non-Dim, 3000K
LC8733BD	ASTON MK-II 67W Suspended, 45W Direct/ 22W Indirect, Black, 85°, DALI, 3000K
LC8733W	ASTON MK-II 67W Suspended, 45W Direct/ 22W Indirect, White, 85°, Non-Dim, 3000K
LC8733WD	ASTON MK-II 67W Suspended, 45W Direct/ 22W Indirect, White, 85°, DALI, 3000K
LC8734B	ASTON MK-II 67W Suspended, 45W Direct/ 22W Indirect, Black, 85°, Non-Dim, 4000K
LC8734BD	ASTON MK-II 67W Suspended, 45W Direct/ 22W Indirect, Black, 85°, DALI, 4000K
LC8734W	ASTON MK-II 67W Suspended, 45W Direct/ 22W Indirect, White, 85°, Non-Dim, 4000K
LC8734WD	ASTON MK-II 67W Suspended, 45W Direct/ 22W Indirect, White, 85°, DALI, 4000K

Classic Series

Proven. Quality. Customisable