

ASTON MK-II 67W

Suspended Direct/Indirect 1681mm

The ASTON MK-II 67W Linear Series are a sleek, modern style perfect for commercial architecture. With a thin profile, this style is available in suspended, surface mounted and recessed.

The ASTON MK-II 67W Linear Direct/Indirect Pendant 1681mm is ideal for offices with higher ceilings. It creates a great ambient light, as well as providing focus below the fitting.







SPECIFICATIONS

Material Specifications

Material 1.0mm Aluminium Housing, with Opal Acrylic

Diffuser

Colour Powdercoat, Black or White

Ingress Protection IP44

Dimensions $1681 \text{mm(L)} \times 65 \text{mm(W)} \times 88 \text{mm(D)}$

Suspension Length 2000mm

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Osram LED Driver

Input Voltage 240V

Optic Specifications

Light Source 45W Direct/ 22W Indirect, Epistar SMD 5630

 Nominal Lumens
 6910lm

 CRI
 > 80Ra

 Beam Angle
 85°

 Colour Deviation
 SDCM ≤ 3

Reported L70 (Hours) > 54,000 Hrs

VARIATIONS

LC8733B ASTON MK-II 67W Suspended, 45W Direct/ 22W Indirect, Black, 85°,

Non-Dim, 3000K

LC8733BD ASTON MK-II 67W Suspended, 45W Direct/ 22W Indirect, Black, 85°,

DALI, 3000K

LC8733S ASTON MK-II 67W Suspended, 45W Direct/ 22W Indirect, Silver, 85°,

Non-Dim, 3000K

LC8733SD ASTON MK-II 67W Suspended, 45W Direct/ 22W Indirect, Silver, 85°, DALI, 3000K

DALI, 3000K

LC8733W ASTON MK-II 67W Suspended, 45W Direct/ 22W Indirect, White, 85°, Non-Dim, 3000K

Non-Dim, 3000K ASTON MK-II 67W Suspended, 45W Direct/ 22W Indirect, White, 85°,

DALI, 3000K

ASTON MK-II 67W Suspended, 45W Direct/ 22W Indirect, Black, 85°, Non-Dim 4000K

LC8734BD ASTON MK-II 67W Suspended, 45W Direct/ 22W Indirect, Black, 85°,

DALI, 4000K









LC8733WD

LC8734B



LC8734S ASTON MK-II 67W Suspended, 45W Direct/ 22W Indirect, Silver, 85°,

Non-Dim, 4000K

LC8734SD ASTON MK-II 67W Suspended, 45W Direct/ 22W Indirect, Silver, 85°,

DALI, 4000K

LC8734W ASTON MK-II 67W Suspended, 45W Direct/ 22W Indirect, White, 85°,

Non-Dim, 4000K

LC8734WD ASTON MK-II 67W Suspended, 45W Direct/ 22W Indirect, White, 85°,

DALI, 4000K

Classic Series
Proven. Quality. Customisable

