

ASTON MK-II 78W

Suspended Direct/Indirect 1961mm

The ASTON MK-II Linear Series are a sleek, modern style perfect for commercial architecture. With a thin profile, this style is available in suspended, surface mounted and recessed.

The ASTON 78W Linear Direct/Indirect Pendant 1965mm is ideal for offices with higher ceilings. It creates a great ambient light, as well as providing focus below the fitting.







SPECIFICATIONS

Material Specifications

Material 1.0mm Aluminium Housing, with Opal Acrylic

Diffuser

Colour Powdercoat, Black or White

Ingress Protection

Dimensions 1961mm(L) x 65mm(W) x 88mm(D)

Suspension Length 1200mm

Warranty 5 Year Replacement

Electrical Specifications

Osram LED Driver, Non-Dimmable **Power Supply**

Input Voltage 240V

Optic Specifications

52W Direct/ 26W Indirect, Epistar SMD 5630 **Light Source Nominal Lumens** 8,048lm (5365lm Down / 2683lm Up)

CRI 80Ra 85° **Beam Angle Colour Deviation** SDCM ≤ 3 Reported L70 (Hours) > 54,000 Hrs

VARIATIONS

LC8743B ASTON MK-II 78W Suspended, 52W Direct/ 26W Indirect, Black, 85°,

Non-Dim, 3000K

ASTON MK-II 78W Suspended, 52W Direct/ 26W Indirect, Black, 85°, LC8743BD

DALI. 3000K

LC8743S ASTON MK-II 78W Suspended, 52W Direct/ 26W Indirect, Silver, 85°,

Non-Dim. 3000K

LC8743SD ASTON MK-II 78W Suspended, 52W Direct/ 26W Indirect, Silver, 85°, **DALI, 3000K**

ASTON MK-II 78W Suspended, 52W Direct/ 26W Indirect, White, 85°,

Non-Dim, 3000K LC8743WD

ASTON MK-II 78W Suspended, 52W Direct/ 26W Indirect, White, 85°, **DALI. 3000K**

LC8744B ASTON MK-II 78W Suspended, 52W Direct/ 26W Indirect, Black, 85°,

Non-Dim 4000K

LC8744BD ASTON MK-II 78W Suspended, 52W Direct/ 26W Indirect, Black, 85°,

DALL 4000K









LC8743W



LC8744S ASTON MK-II 78W Suspended, 52W Direct/ 26W Indirect, Silver, 85°,

Non-Dim, 4000K

LC8744SD ASTON MK-II 78W Suspended, 52W Direct/ 26W Indirect, Silver, 85°,

DALI, 4000K

LC8744W ASTON MK-II 78W Suspended, 52W Direct/ 26W Indirect, White, 85°,

Non-Dim, 4000K

LC8744WD ASTON MK-II 78W Suspended, 52W Direct/ 26W Indirect, White, 85°,

DALI, 4000K

Classic Series
Proven. Quality. Customisable

