

Classic Series

Proven. Quality. Customisable

ASTON MK-II 90W

Suspended Direct/ Indirect

The ASTON Linear Series are a sleek, modern style perfect for commercial architecture. With a thin profile, this style is available in suspended, surface mounted and recessed.

The ASTON 90W Linear Direct/ Indirect Pendant 2245mm is ideal for offices with higher ceilings. It creates a great ambient light, as well as providing focus below the fitting.



IP40



SPECIFICATIONS

Material Specifications

Material	1.0mm Aluminium Housing, with Opal Acrylic Diffuser
Finish	Powder Coat
Ingress Protection	IP40
Dimensions	2241mm(L) x 62mm(W) x 82mm(D)
Suspension Length	2000mm
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Osram LED Driver
Input Voltage	240V

Optic Specifications

Light Source	60W Direct/ 30W Indirect, Epistar SMD 5630
Nominal Lumens	9270lm
CRI	>80Ra
Beam Angle	85°
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	>54,000 Hrs

VARIATIONS

LC8753B	ASTON MK-II 90W Suspended, 60W Direct/ 30W Indirect, Black, 85°, Non-Dim, 3000K
LC8753BD	ASTON MK-II 90W Suspended, 60W Direct/ 30W Indirect, Black, 85°, DALI, 3000K
LC8753W	ASTON MK-II 90W Suspended, 60W Direct/ 30W Indirect, White, 85°, Non-Dim, 3000K
LC8753WD	ASTON MK-II 90W Suspended, 60W Direct/ 30W Indirect, White, 85°, DALI, 3000K
LC8754B	ASTON MK-II 90W Suspended, 60W Direct/ 30W Indirect, Black, 85°, Non-Dim, 4000K
LC8754BD	ASTON MK-II 90W Suspended, 60W Direct/ 30W Indirect, Black, 85°, DALI, 4000K
LC8754W	ASTON MK-II 90W Suspended, 60W Direct/ 30W Indirect, White, 85°, Non-Dim, 4000K
LC8754WD	ASTON MK-II 90W Suspended, 60W Direct/ 30W Indirect, White, 85°, DALI, 4000K

Classic Series

Proven. Quality. Customisable