

ASTON MK-II 90W

Suspended Direct/Indirect

The ASTON Linear Series are a sleek, modern style perfect for commercial architecture. With a thin profile, this style is available in suspended, surface mounted and recessed.

The ASTON 90W Linear Direct/ Indirect Pendant 2245mm is ideal for offices with higher ceilings. It creates a great ambient light, as well as providing focus below the fitting.



IP40



SPECIFICATIONS

Material Specifications

Material 1.0mm Aluminium Housing, with Opal Acrylic

Diffuser

Finish Powder Coat

Ingress Protection IP40

Dimensions 2241mm(L) x 62mm(W) x 82mm(D)

Suspension Length 2000mm

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Osram LED Driver

Input Voltage 240V

Optic Specifications

Light Source 60W Direct/ 30W Indirect, Epistar SMD 5630

 Nominal Lumens
 9270 lm

 CRI
 >80 Ra

 Beam Angle
 85°

 Colour Deviation
 SDCM ≤ 3

 Reported L70 (Hours)
 >54,000 Hrs

VARIATIONS

LC8753B ASTON MK-II 90W Suspended, 60W Direct/ 30W Indirect, Black, 85°,

Non-Dim, 3000K

LC8753BD ASTON MK-II 90W Suspended, 60W Direct/ 30W Indirect, Black, 85°,

DALI, 3000K

LC8753W ASTON MK-II 90W Suspended, 60W Direct/ 30W Indirect, White, 85°,

Non-Dim, 3000K

LC8753WD ASTON MK-II 90W Suspended, 60W Direct/ 30W Indirect, White, 85°,

DALI, 3000K

LC8754B ASTON MK-II 90W Suspended, 60W Direct/ 30W Indirect, Black, 85°,

Non-Dim, 4000K

LC8754BD ASTON MK-II 90W Suspended, 60W Direct/ 30W Indirect, Black, 85°, DALI. 4000K

DALI, 4000K

LC8754W ASTON MK-II 90W Suspended, 60W Direct/ 30W Indirect, White, 85°,

Non-Dim, 4000K

LC8754WD ASTON MK-II 90W Suspended, 60W Direct/ 30W Indirect, White, 85°,

DALI, 4000K









Classic Series Proven. Quality. Customisable

