

Classic Series

Proven. Quality. Customisable

BLAIZE 24W

Rectangle Panel Light 1200x300

The BLAIZE 24W Panel Light 1200x300 is at the leading edge of commercial lighting. With an optical diffuser, the LED panel light delivers a smooth, flawless wall of illumination without visible bulbs or hot spots. Mount with our suspension kit, plaster recess kit or surface mount kit. Dimmable driver available.



IP44



Flicker Free



SPECIFICATIONS

Material Specifications


Material	White Aluminium Frame. PMMA
Dimensions	1195mm (L) x 295mm (W) x 12mm (D)
Ingress Protection	IP44
Warranty	5 Year Replacement
Weight	3.2Kg
Accessories	Surface Mount, Plaster Recess & Suspension Kits

Electrical Specifications

Power Supply	Non-Dimmable Boke Remote Driver
Options	DALI Available
Connection Method	Australian 2-Pin Plug & 1.0m Lead
Input Voltage	240V
Operating Temperature (Ta)	-20°C to +45°C

Optic Specifications

Light Source	24W Epistar, 2-side Edge lit
Efficacy	120lm/W
Nominal Lumens	2,880lm (4000K)
Nominal Lumens	2,730lm (3000K)
CRI	> 80Ra
Reported L70 (Hours)	> 54,000 Hours



VARIATIONS

LC7201	BLAIZE 24W 1200x300 Panel Light, White, 120°, Non-Dim, 3000K
LC7201D	BLAIZE 24W 1200x300 Panel Light, White, 120°, DALI, 3000K
LC7202	BLAIZE 24W 1200x300 Panel Light, White, 120°, Non-Dim, 4000K
LC7202D	BLAIZE 24W 1200x300 Panel Light, White, 120°, DALI, 4000K