

BLAIZE 40W

Rectangle Panel Light 1200x300

The BLAIZE 40W LED Panel Light is at the leading edge of commercial lighting. Use this 2' x 4' rectangular LED panel light for office lighting, basement lighting, gym lighting, school lighting and hospital lighting! BLAIZE LED light panels are designed for residential and commercial suspended grid ceilings. Replace existing fluorescent troffer light fixtures or use for new construction applications. Eliminate maintenance costs and enjoy a high efficiency light source. With an optical diffuser, the LED panel light delivers a smooth, flawless wall of illumination without visible bulbs or hot spots. Mount with our suspension kit, plaster recess kit or surface mount kit. Dimmable driver available.





Flicker



Material Specifications

Material White Aluminium Frame, PMMA **Dimensions** 1195mm (L) x 295mm (W) x 12mm (D)

Ingress Protection IP44

Warranty 5 Year Replacement

Weight

Accessories Surface Mount, Plaster Recess & Suspension Kits

Electrical Specifications

Non-Dim Boke Remote Driver **Power Supply**

Options DALI Available

Connection Method Australian 2-Pin Plug & 1.2m Lead

Input Voltage 240V

Operating Temperature (Ta) -20°C to +45°C

Optic Specifications

Light Source 40W Epistar, 2-side Edge lit

4,750lm (4000K) Nominal Lumens **Nominal Lumens** 4,510lm (3000K)

80Ra

Calculated L70 (Hours) >170.000 Hrs Calculated L80 (Hours) >110.000 Hrs Calculated L90 (Hours) >53,000 Hrs

VARIATIONS

LC7171 BLAIZE 40W 1200x300 Panel Light, White, 120°, Non-Dim, 4000K,

4.750lm

BLAIZE 40W 1200x300 Panel Light, White, 120°, DALI, 4000K, 4,750lm LC7171D

BLAIZE 40W 1200x300 Panel Light, White, 120°, Non-Dim, 3000K, LC7170

LC7170D BLAIZE 40W 1200x300 Panel Light, White, 120°, DALI, 3000K, 4,510lm







