

BURNET 24W Cleanroom

637x337 Panel Light IP54

Classic Series
Proven. Quality. Customisable

The BURNET 24W Cleanroom Panel Light is specifically designed for clean-room environments and other hygienic places. It provides an ideal solution for pharmaceutical, medical, and other sterile areas. The BURNET Cleanroom Panel Light is named after Mr Frank Burnet, An Australian virologist best known for his contributions to immunology.

2-sides edge-lit for improved heat dissipation and longer lifespan. 100% PMMA Light Guide Plate, to avoid yellowing over time. Flicker-Free Driver. Bevel Edge Design, to eliminate dust build-up.

Surface Mount Design. 12mm depth. For an easy install, make a 90mm cutout in the ceiling, to recess the LED driver in the ceiling cavity.

Verified by Techlume Australia on 26/07/2025









SPECIFICATIONS

Material Specifications

Material White Aluminium Frame RAL9016. PMMA

Dimensions 637mm x 337mm x 12mm

Ingress Protection IP54

Warranty 5 Year Replacement

Weight 3.4 Kg

Electrical Specifications

Power Supply MIHN2036YB-C0750A

System Watts 25.0W

Connection Method Australian 2-Pin Plug & 1.0m Lead

Input Voltage 240V

Operating Temperature (Ta) -25°C to +40°C

Optic Specifications

Light Source 4014-JT-K1606 Series **Nominal Lumens** 2,455lm (4000K) Up to 98lm/W **Efficacy CRI** Ra >80 120° **Beam Angle** UGR <22 **Colour Deviation** SDCM <3 Calculated L70 (Hours) >170,000 Hrs Calculated L80 (Hours) >110.000 Hrs Calculated L90 (Hours) >53,000 Hrs

VARIATIONS

 LC7402
 BURNET 24W 637x337 Panel Light, White, Non-Dim, 4000K, 2,455lm

 LC7402D
 BURNET 24W 637x337 Panel Light, White, DALI, 4000K, 2,455lm

 LC7403
 BURNET 24W 637x337 Panel Light, White, Non-Dim, 5700K



1300 827 284 sales@decrolux.com.au | Latest Product Data >



Classic Series Proven. Quality. Customisable

