

BURNET 40W Cleanroom


Panel Light, IP54, 632x632mm

Classic Series

Proven. Quality. Customisable

The BURNET 30W Cleanroom Panel Light is specifically designed for clean-room environments and other hygienic places. A recessed IP65 LED cleanroom luminaire with opal acrylic diffuser provides an ideal solution for pharmaceutical, medical, and other sterile areas. The frame is fitted into the body with four stainless steel screws to provide reliable ingress protection.

The BURNET Cleanroom Panel Light is named after Mr Frank Burnet, An Australian virologist best known for his contributions to immunology.

**IP54**

SPECIFICATIONS

Material Specifications

| | |
|---------------------------|--|
| Material | Steel Sheet Body, Opal Acrylic Diffuser, UV Stable, Chemically Resistant |
| Dimensions | 632mm x 632mm x 75mm |
| Ingress Protection | IP54 |
| Impact Rating | IK05 |
| Warranty | 5 Year Replacement |
| Weight | 4.5Kg |

Electrical Specifications

| | |
|-----------------------------------|-----------------------------------|
| Power Supply | Non-Dim Boke Remote Driver |
| Connection Method | Australian 2-Pin Plug & 1.0m Lead |
| Input Voltage | 220-240V, 50-60Hz |
| Operating Temperature (Ta) | -10°C to +35°C |

Optic Specifications

| | |
|--------------------------------|--------------------------|
| Light Source | 30W LED, 2-side Edge lit |
| Delivered Lumens | 4,278lm (4000K) |
| CRI | 80Ra |
| Beam Angle | 120° |
| Colour Deviation | SDCM ≤ 3 |
| Rated Lifetime (L80B10) | 55,000 Hrs |

VARIATIONS

| | |
|----------------|---|
| LC7417 | BURNET 40W 632x632 Panel Light, Non-Dim, 4000K, 4,278lm |
| LC7417D | BURNET 40W 632x632 Panel Light, DALI, 4000K, 4,278lm |