

# BURNET 40W Cleanroom 1237x337 Panel Light IP54

Classic Series
Proven. Quality. Customisable

BURNET 40W Cleanroom 1200x300 Panel Light is specifically designed for cleanroom environments and other hygienic places. The BURNET Cleanroom Panel Light is named after Mr Frank Burnet, an Australian virologist best known for his contributions to immunology.

2-sides edge-lit for improved heat dissipation and longer lifespan. 100% PMMA Light Guide Plate, to avoid yellowing over time. Flicker-Free Driver. Bevel Edge Design, to eliminate dust build-up. Surface Mount Design, 12mm depth. For an easy install, make a 90mm cutout in the ceiling, to recess the LED driver in the ceiling cavity.













# **SPECIFICATIONS**

### **Material Specifications**

Material White Aluminium Frame RAL9016. PMMA

Mounting Surface Mounted

**Dimensions** 1237mm x 337mm x 12mm

Ingress Protection IP54

Warranty 5 Year Replacement

Weight 3.4Kg

### **Electrical Specifications**

Power Supply MIHN2040YB-C1000A

System Watts 38.3W

**Connection Method** Australian 2-Pin Plug & 1.0m Lead

Input Voltage 240V

Operating Temperature (Ta) -25°C to +40°C

## **Optic Specifications**

**Light Source** 4014-JT-K1606 Series, 40W LED 2-side Edge lit

 Delivered Lumens
 4,407lm (4000K)

 Efficacy
 Up to 116lm/W

 CRI
 Ra >80

 Beam Angle
 120°

 UGR
 <22</td>

 Colour Deviation
 SDCM <3</td>

 Calculated L70 (Hours)
 >170,000 Hrs

VARIATIONS

Calculated L80 (Hours)

Calculated L90 (Hours)

**LC7415** BURNET 40W 1237x337 Panel Light, White, 120°, Non-Dim, 4000K,


4,407lm

**LC7415D**BURNET 40W 1237x337 Panel Light, White, 120°, DALI, 4000K, 4,407lm **LC7416**BURNET 40W 1237x337 Panel Light, White, 120°, Non-Dim, 5700K,

>110,000 Hrs

>53,000 Hrs

4,345lm







**Classic Series** Proven. Quality. Customisable

