

# CADE 20W

## 600mm Surface Mount Batten

dynamic series

Efficient. Cutting Edge. Reliable

LED Battens are an awesome new LED solution to replace standard fluorescent battens. Designed to be surface mounted. Very slim aesthetic design. Available in both Warm and Cool White, and 20W and 40W options.

The CADE slimline 20W batten is the perfect LED replacement for surface mounted fluorescent light fittings or other surface mounted installations. A 5 year warranty proves that it can stand the test of time.

Verified by Techlume Australia on 09/10/2023



IP44



### SPECIFICATIONS

#### Material Specifications

<b>Material</b>	6063 Aluminum housing + PC cover + PC end caps
<b>Finish</b>	White Powdercoat
<b>Dimensions</b>	80mm (W) x 35mm (H) x 580mm (L)
<b>Ingress Protection</b>	IP44
<b>Impact Rating</b>	IK05
<b>Warranty</b>	5 Year Replacement

#### Electrical Specifications

<b>Power Supply</b>	Integral, Non-Dimmable, 260mA
<b>Input Voltage</b>	240V
<b>System Watts</b>	19.3W - 20.3W
<b>Connection Method</b>	End Terminal Block
<b>Operating Temperature (Ta)</b>	-20°C to +45°C

#### Optic Specifications

<b>Light Source</b>	Epistar SMD x 100
<b>Correlated Colour Temperature</b>	Tri-colour: 3000K/4000K/6000K
<b>Optics</b>	Frosted Diffuser
<b>Delivered Lumens</b>	1,956lm (3000K)
<b>Delivered Lumens</b>	2,238lm (4000K)
<b>Delivered Lumens</b>	2,042lm (6000K)
<b>Efficacy</b>	Up to 115.8 lm/W
<b>Beam Angle</b>	115°
<b>CRI</b>	Ra >81
<b>Rated Lifetime (L70B20)</b>	40,000 Hrs



### VARIATIONS

<b>LC2389</b>	CADE 20W Linear Surface Batten, White, 115°, Non-Dim, Tri-Colour
---------------	--