

CARDIFF

60W Solar Streetlight

Classic Series
Proven. Quality. Customisable

The Compact Solar Lighting Solution. Decrolux presents the ultimate fully integrated solar street light system, with an extremely simple installation method.

Fully Automatic operation, the Light turns on in the evening, and switches off in the morning, by detecting daylight. Motion sensor detects movement powers up to 100%. With no movement, it dims to 50%. Over 24 hours use at Full Charge, with a charging time of 6-7 hours.

Typical installation time of 30 minutes. No power consumption, no cables required.



IP66

SPECIFICATIONS

Material Specifications

MaterialAluminium Alloy Body CaseDimensions1570mm x 455mm x 240mm

Spigot Size95mmIngress ProtectionIP66Weight19.2Kg

Accessories Anti-Theft Screws

Mounting Height 4m - 7m

Warranty 5 Year Replacement

Electrical Specifications

Solar Panel 105W, 18V Monocrystal Panel, Grade A 25 Years

Operating Temperature (Ta) -10°C to +60°C

Working Time > 20 Hrs/ Day, 4 Rainy Days

Battery 42Ah 12.8V Lithium LIFEPO4

Optic Specifications

Light Source 60W Lumileds Luxeon LED 3030, Qty 40

 Nominal Lumens
 9,052lm

 Beam Angle
 120°

 CRI
 >75Ra

 Rated Lifetime (L80B20)
 >50,000 Hrs

Spigot Size 95MM to suit 89mm 0D

VARIATIONS

LC6620 CARDIFF 60W Solar Streetlight, 120°, 3000K, 9,052lm **LC6621** CARDIFF 60W Solar Streetlight, 120°, 4000K, 9,052lm



