

CARDIFF 80W Solar Streetlight

Classic Series
Proven. Quality. Customisable

The Compact Solar Lighting Solution. Decrolux presents the ultimate fully integrated solar street light system, with an extremely simple installation method.

Fully Automatic operation, the Light turns on in the evening, and switches off in the morning, by detecting daylight. Motion sensor detects movement powers up to 100%. With no movement, it dims to 50%. Over 24 hours use at Full Charge, with a charging time of 6-7 hours.

Typical installation time of 30 minutes. No power consumption, no cables required.



IP65

SPECIFICATIONS

Material Specifications

MaterialAluminium Alloy Body CaseDimensions1570mm x 455mm x 240mm

Ingress ProtectionIP65Weight19.2Kg

Accessories Anti-Theft Screws

 $\begin{tabular}{ll} \textbf{Mounting Height} & 4m-7m \end{tabular}$

Warranty 5 Year Replacement

Electrical Specifications

Solar Panel 130W, 18V Monocrystal Panel, Grade A 25 Years

Operating Temperature (Ta) -10°C to +60°C

Working Time > 20 Hrs/ Day, 4 Rainy Days

Battery 54Ah 12.8V Lithium LIFEPO4

Optic Specifications

Light Source 80W Lumileds Luxeon LED 3030, Qty 40

 Nominal Lumens
 12,449lm

 CRI
 >75Ra

 Rated Lifetime (L80B20)
 >50,000 Hrs

 Spigot Size
 Suits 76mm 0D

VARIATIONS

LC6685-T2 CARDIFF 80W Solar Streetlight, T2 Optic, 5000K, 12,449lm

