

dynamic series

Efficient. Cutting Edge. Reliable

ECLIPSE 25W IP54

Round Surface Can Light

ECLIPSE 25W surface mounted ceiling light adopts COB led chip. Aluminium profile provides excellent thermal dissipation. Isolated driver solution both in dimmable and non-dimmable version achieves stable working performance.

Application: Suitable for commercial and residential applications like office, supermarket, shop, school, hotel, restaurant, workshop, warehouse, home etc.



SPECIFICATIONS

Material Specifications

Material	Die-Cast Aluminium
Colour	White RAL9016 / Black RAL9005
Dimensions	160mm (Dia) x 120mm (H)
Ingress Protection	IP54
Warranty	5 Year Replacement

Electrical Specifications

Optics	60° Standard (24° / 36° / 45° available to Order)
Input Voltage	240V
Power Supply	Integral Driver, 230mA
Connection Method	Terminal Block in base
Operating Temperature (Ta)	-20°C to 40°C

Optic Specifications

Light Source	Citizen 25W LED
CRI	> 80Ra
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	> 50,000 Hrs
Correlated Colour Temperature	3000K / 4000K Standard (2700K / 5000K available to Order)



VARIATIONS

LC3532	ECLIPSE 25W Surface Mount Can Light, White, 60°, Non-Dim, 3000K, 2650lm
LC3532D	ECLIPSE 25W Surface Mount Can Light, White, 60°, DALI, 3000K, 2650lm
LC3534	ECLIPSE 25W Surface Mount Can Light, Black, 60°, Non-Dim, 3000K, 2650lm
LC3534D	ECLIPSE 25W Surface Mount Can Light, Black, 60°, DALI, 3000K, 2650lm
LC3536	ECLIPSE 25W Surface Mount Can Light, White, 60°, Non-Dim, 4000K, 2845lm
LC3536D	ECLIPSE 25W Surface Mount Can Light, White, 60°, DALI, 4000K, 2845lm
LC3538	ECLIPSE 25W Surface Mount Can Light, Black, 60°, Non-Dim, 4000K, 2845lm
LC3538D	ECLIPSE 25W Surface Mount Can Light, Black, 60°, DALI, 4000K, 2845lm

dynamic series

Efficient. Cutting Edge. Reliable