

# **CREST 18W**

# UGR<19 Panel Light 600x300

The CREST 18W Panel Light 600x300 is at the leading edge of commercial lighting. Suitable for surface mounting or recessed or suspended. Eliminate maintenance costs and enjoy a high-efficiency light source. DALI Dimmable driver is available. This LED panel light is a brilliant light that offers high performance combined with affordability and sustainability.

Verified by Techlume Australia on 25/08/2023







#### **SPECIFICATIONS**

#### **Material Specifications**

MaterialWhite Aluminium Frame. PMMADimensions295mm x 12mm

Ingress ProtectionIP44Weight2.2Kg

**Options** Surface Mount, Plaster Recess & Suspension Kits

Warranty 5 Year Replacement

#### **Electrical Specifications**

**Power Supply** Non-Dimmable Boke Remote Driver

**Connection Method** Australian 2-Pin Plug & 1.2m Lead

**Operating Temperature (Ta)** -20°C to +45°C

### **Optic Specifications**

**Light Source** Epistar, 2-side Edge lit

Delivered LumensUp to 2,266ImEfficacyUp to 130.4 Im/W

CRI Ra 80 (Ra 90 available for project orders)

 Beam Angle
 80°

 Colour Deviation
 SDCM ≤ 3

 Calculated L70 (Hours)
 >170,000 Hrs

 Calculated L80 (Hours)
 >110,000 Hrs

 Calculated L90 (Hours)
 >53,000 Hrs

## **VARIATIONS**

**LC7190** CREST 18W LED Anti-Glare Panel Light 600x300, White, 80°, Non-Dim,

4000K, 2,266lm

LC7190R CREST 18W LED Anti-Glare Panel Light 600x300, White, 80°, Non-Dim,

4000K, CRI >90, 1,926lm

LC7190D CREST 18W LED Anti-Glare Panel Light 600x300, White, 80°, DALI Dim,

4000K, 2,266lm







