

CREST 24W

UGR<19 Panel Light 1200x300

The CREST 24W Panel Light 1200x300 is a high performing panel light designed with a micro prismatic diffuser which perfects the balance between light distribution, low glare, and visual appeal. Available in emergency and dimmable options. Superior Optical Design, Quick + Easy Retrofit, Flicker + Glare Free, Engineered to Perfection.









Flicker Free

SPECIFICATIONS

Material Specifications

Material Aluminium Edgefold Back Sheet

Finish White

Dimensions 1195mm (L) x 295mm (W) x 10mm (D)

Ingress Protection IP44

Accessories Surface Mount Kits, Plaster Recessed Kits,

Suspension Kits

Weight 3kg

Warranty 5 Year Warranty

Electrical Specifications

Power Supply Non-Dim Driver (Flicker Free)

Input Voltage 240V

Connection Method Australian 2-Pin Plug & 1.2m Lead

Operating Temperature (Ta) -20°C to +45°C

Optic Specifications

OpticsPMMA LGPDelivered LumensUp to 3,416lm

CRI Ra 80 (Ra 90 available for project orders)

 Calculated L70 (Hours)
 >170,000 Hrs

 Calculated L80 (Hours)
 >110,000 Hrs

 Calculated L90 (Hours)
 >53,000 Hrs

 Light Source
 2 Sides Edge-lit

VARIATIONS

LC7211 CREST 24W Anti-Glare Panel Light 1200x300, 100°, Non-Dim, 3000K,

3,192lm

LC7212 CREST 24W Anti-Glare Panel Light 1200x300, 100°, Non-Dim, 4000K,

3,416lm

LC7212R CREST 24W Anti-Glare Panel Light 1200x300, 100°, Non-Dim, 4000K,

CRI >90, 2,903lm

LC7212D CREST 24W Anti-Glare Panel Light 1200x300, CREST 24W Anti-Glare

Panel Light 1200x300, DALI2, 4000K, 3,416lm







