

Dx 6W

Exterior Projector Light

diomede

let there be light

The Diomede Dx 6W Projector Light is available as surface or spike mounted, adjustable spot luminaire, anodised aluminium with tempered glass and aluminium honeycomb lens.

Dx - Spot luminaire turned anodised aluminium, silicone glued tempered glass, silicone gaskets, aluminium honeycomb, metal cable gland M12x1.5/ M10x1.45, neoprene 2 poles cables H05RN-F. Premium Quality, Italian Made product.

Available in anodised bronze and anodised aluminium. Also available in a smaller size.



SPECIFICATIONS

Material Specifications

Material	Anodised Aluminium, Tempered Glass
Dimensions	85mm (Dia) x 60mm
Ingress Protection	IP65
Accessories	Stake Mounting Included
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	IP67 Remote Driver, Sold Separately
Max. Loading	4.5W
Input Voltage	24V

Optic Specifications

Light Source	5W CREE LED
Optics	Aluminium Honeycomb Lens
CRI	83Ra
Reported L70 (Hours)	> 50,000 Hrs



VARIATIONS

900412036	Dx 6W Projector Light 24V, Anodised Aluminium, 26°, 3000K, 264lm
900412039	Dx 6W Projector Light 24V, Anodised Bronze, 26°, 3000K, 264lm
900412046	Dx 6W Projector Light 24V, Anodised Aluminium, 52°, 3000K, 142lm
900412047	Dx 6W Projector Light 24V, Anodised Bronze, 52°, 3000K, 142lm