

dynamic series

Efficient. Cutting Edge. Reliable

# ECLIPSE 25W IP54

## Round Surface Can Light

ECLIPSE 25W surface mounted ceiling light adopts COB led chip. Aluminium profile provides excellent thermal dissipation. Isolated driver solution both in dimmable and non-dimmable version achieves stable working performance.

Application: Suitable for commercial and residential applications like office, supermarket, shop, school, hotel, restaurant, workshop, warehouse, home etc.



### SPECIFICATIONS

#### Material Specifications

<b>Material</b>	Die-Cast Aluminium
<b>Colour</b>	White RAL9016 / Black RAL9005
<b>Dimensions</b>	160mm (Dia) x 120mm (H)
<b>Ingress Protection</b>	IP54
<b>Warranty</b>	5 Year Replacement

#### Electrical Specifications

<b>Optics</b>	60° Standard (24° / 36° / 45° available to Order)
<b>Input Voltage</b>	240V
<b>Power Supply</b>	Integral Driver, 230mA
<b>Connection Method</b>	Terminal Block in base
<b>Operating Temperature (Ta)</b>	-20°C to 40°C

#### Optic Specifications

<b>Light Source</b>	Citizen 25W LED
<b>CRI</b>	> 80Ra
<b>Colour Deviation</b>	SDCM ≤ 3
<b>Reported L70 (Hours)</b>	> 50,000 Hrs
<b>Correlated Colour Temperature</b>	3000K / 4000K Standard (2700K / 5000K available to Order)



### VARIATIONS

<b>LC3532</b>	ECLIPSE 25W Surface Mount Can Light, White, 60°, Non-Dim, 3000K, 2650lm
<b>LC3532D</b>	ECLIPSE 25W Surface Mount Can Light, White, 60°, DALI, 3000K, 2650lm
<b>LC3534</b>	ECLIPSE 25W Surface Mount Can Light, Black, 60°, Non-Dim, 3000K, 2650lm
<b>LC3534D</b>	ECLIPSE 25W Surface Mount Can Light, Black, 60°, DALI, 3000K, 2650lm
<b>LC3536</b>	ECLIPSE 25W Surface Mount Can Light, White, 60°, Non-Dim, 4000K, 2845lm
<b>LC3536D</b>	ECLIPSE 25W Surface Mount Can Light, White, 60°, DALI, 4000K, 2845lm
<b>LC3538</b>	ECLIPSE 25W Surface Mount Can Light, Black, 60°, Non-Dim, 4000K, 2845lm
<b>LC3538D</b>	ECLIPSE 25W Surface Mount Can Light, Black, 60°, DALI, 4000K, 2845lm

**dynamic series**

Efficient. Cutting Edge. Reliable