

EMPRESS 10W

Recessed Fixed Downlight

The EMPRESS Fixed Recessed Downlight is used in commercial projects, as a comfortable and efficient lighting solution. A compact architectural downlight suitable for a variety of applications. It adopts a high lumen COB LED, and PMMA diffuser with even light output. The dali dimmable version has shown great popularity with excellent dimming effect.

Verified by Techlume Australia on 30/03/2023









dynamic series

Efficient. Cutting Edge. Reliable

SPECIFICATIONS

Material Specifications

MaterialHigh Grade Aluminum + ReflectorDimensions110mm Face Dia x 65mm (H)

Cutout 90mm (Dia)

Colour Matt White (Black & Silver available for project

orders)

Ingress ProtectionIP65Impact RatingIK06

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Dimmable 23-40VDC 230mA, DALI options

System Watts 10.1W

 $\begin{tabular}{ll} \mbox{Input Voltage} & 240\mbox{V}, 50\mbox{/}60\mbox{Hz} \\ \mbox{Operating Temperature (Ta)} & -20\mbox{°C to } +45\mbox{°C} \\ \end{tabular}$

Thermal TestingCompliant with IC Classification
Connection Method
Australian Plug & 1.2m Lead

Protection Voltage Overload, Temp Overload, Short Circuit

Optic Specifications

Light Source CREE CXA1507 COB LED

Efficacy Up to 105.8 lm/W

CRI Ra >83

Beam Angle 60° (36° Available for Project Order)

 Calculated L70 (Hours)
 160,000 Hrs

 Calculated L80 (Hours)
 100,000 Hrs

 Calculated L90 (Hours)
 45,000 Hrs

VARIATIONS

LC3595 EMPRESS 10W Fixed Downlight, White, 60°, Phase Dim, 3000K, 1,004lm LC3595B EMPRESS 10W Fixed Downlight, Black, 60°, Phase Dim, 3000K, 1,004lm LC3596 EMPRESS 10W Fixed Downlight, White, 60°, Phase Dim, 4000K, 1,066lm LC3596B EMPRESS 10W Fixed Downlight, Black, 60°, Phase Dim, 4000K, 1,066lm



