dynamic series

Efficient. Cutting Edge. Reliable



EMPRESS 13W

Recessed Gimbal Downlight

The EMPRESS 13W gimbal downlight is available in DALI dimmable, constructed with a thermal heatsink included to ensure the downlight disperses any heat keeping it cool to touch. Used by builders, developers and a favourite with

EMPRESS 13W LED gimbal Downlight adopts a high lumen COB LED, and PMMA diffuser with even light output. DALI dimmable version has shown great popularity with excellent dimming effect.

Verified by Techlume Australia on 23/03/2023



electricians.









SPECIFICATIONS

Material Specifications

Material High Grade Aluminum + Reflector

Adjustment 30° gimbal

Dimensions 110mm Face Dia x 50mm (H)

Cutout 90mm (Dia)

Colour Matt White (Black & Silver available for project

orders)

Ingress ProtectionIP65Impact RatingIK06

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Dimmable, 23-40VDC 280mA

Thermal Testing Compliant with IC Classification

Protection Voltage Overload, Temp Overload, Short Circuit

Connection Method Australian Plug & 1.2m Lead

Optic Specifications

Light Source CREE XLamp® CXA-1512

 Delivered Lumens
 1,256lm (3000K)

 Delivered Lumens
 1,394lm (4000K)

 Efficacy
 Up to 115.4 lm/W

CRI Ra 83

Beam Angle 60° (36° Available for Project Order)

 Calculated L70 (Hours)
 L70B50 = >60,000 Hrs


 Calculated L80 (Hours)
 L80B50 = >60,000 Hrs

 Calculated L90 (Hours)
 L90B50 = >56,000 Hrs

VARIATIONS

LC3592 EMPRESS 13W Gimbal Downlight, White, 60°, Phase Dim, 3000K,

1,256lm







EMPRESS 13W Gimbal Downlight, Black, 60°, Phase Dim, 3000K, 1,256lm LC3592B LC3592D EMPRESS 13W Gimbal Downlight, White, 60°, Dali, 3000K, 1,256lm EMPRESS 13W Gimbal Downlight, White, 60°, Phase Dim, 4000K, LC3593

1,394lm

LC3593B EMPRESS 13W Gimbal Downlight, Black, 60°, Phase Dim, 4000K, 1,394lm dynamic series Efficient. Cutting Edge. Reliable

